

## INTERACTIVE SCREEN Avtek Touchscreen 5 Business 65"



Present | Teach | Inspire



## Avtek Touchscreen 5 Business 65"

## Technical specification

Avtek TouchScreen 5 Business interactive screen is made for huddle rooms and small to medium conference rooms. It stands out with it's elegant, flat design and wide functionality. Touch is recognized by capacitive sensing, an intelligent technology that not only makes writing experience the most natural but also recognizes touch pressure and can differentiate between palm and pen. Thanks to that users can comfortably rest their palm on the screen while writing.

TouchScreen 5 Business users can download apps from AvtekApps store and the conveniently add them to their desktop, which can be customized by adding apps and widgets to it. Business model is equipped with WiFi and Bluetooth connectivity, ScreenShare Pro app for wireless screen sharing and two interactive pens that have configurable buttons and allows for writing with two colors at the same time. New 2+1 speakers with 15W subwoofer are designed for best audio quality in conference room environment.













model(diagonal)         65"           resolution         4K/UHD (3840 × 2160) @60 Hz           display area         1428.5 mm × 803,5 mm           pixel size (pitch)         0,372mm × 0,372 mm           backlight         Direct LED	
display area       1428.5 mm × 803,5 mm         pixel size (pitch)       0,372mm × 0,372 mm	
pixel size (pitch) 0,372mm × 0,372 mm	
backlight Direct LED	
response time 9 ms	
refresh frequency 60 HZ for 4K / UHD (3840 × 2160)	
display colors 1,07 bn (10bit)	
brightness 350 cd/m <sup>2</sup>	
viewing angle 178°	
contrast (typical) 4000:1	
panel life time <b>30 000 hours</b>	
protection glass Toughened Glass with Level 7 of Mohs Standard	
TOUCH SPECS	
technology Capacitive	
touch tool Finger, capacitive pen	
min. object size 1 mm	
supported points 20	
touch resolution 32767 x 32767 points	
response time <20 ms	
precision 1 mm	
supported platforms Windows: 10, 8.1, 8, 7, Vista, XP Linux / Mac / Android / Chrome	
INPUTS/OUTPUTS	
HDMI in 2 × HDMI 2.0 (4K @ 60Hz)	
HDMI out 1	
VGA in 1	
Audio ports 1 × input / 1 × output	
USB ports 4 × USB 2.0 / 1 × USB 3.0	
Including USB ports on the front 1 (shared between OPS, Android and external computer conner by USB Touch)	ted
USB touch 2	
SPDIF in 1	
AV in 1	
RS232 1	
LAN (RJ45) 1 shared port (for OPS and Android)	
Avtek OPS slot Yes (Supports 4K@60Hz)	
built-in speakers 2 × 10 W + 15W subwoofer	



OS version7.0OS resolutionFull HDCPUARM Cortex A73 Dual Core CPUGPUMali-450GBUGBSOFTWARE DETAILS6 GBSOFTWARE DETAILSenglish / german / polishInnotation softwareYes, Note 2.0Innotations on all sourceYes, Note 2.0Innotations on a
CPUARM Cortex A73 Dual Core CPUMaii-450Maii-450CBRAMCBCBSOFTWARE DETAILSIanguagenglish / german / polishannotation softwareYes, Note 2.0Annotations on all sourcesYes, two modesSource name changeYesboot logo uploadYesSource name changeYespossibility to show send and show comments on the screetYeswindows software compatible with built-in annotation toYes, NotePHYSICAL SPECYes, Note
GPUMali-450RAM2 GBROM16 GBSOFTWARE DETAILSIanguageenglish / german / polishannotation softwareYes, Note 2.0annotations on all sourcesYes, two modesboot logo uploadYesSource name changeYespossibility to show send and show comments on the screenYeswindows software compatible with built-in annotation toolYes, NotePHYSICAL SPECYes, Note
RAM ROM2 GBBOM16 GBSOFTWARE DETAILSIanguageenglish / german / polishIannotation softwareYes, Note 2.0Iannotations on all sourcesYes, two modesIannotations on all source name changeYesIannotation software compatible with built-in response systemYesIndows software compatible with built-in annotation toolYesImage: PhySICAL SPECYes, Note
ROM       16 GB         SOFTWARE DETAILS         Ianguage       english / german / polish         Ianguage       english / german / polish         Ianguage       english / german / polish         Ianguage       fes, Note 2.0         Ianguage       fes, two modes         Ianguage       fes, two modes         Ianguage       fes         Ianguage       fes         Ianguage       fes         Ianguage       fes         Ianguage       fes         Ianguage       fes         Ianguage       fes, Note         Ianguage       fes         Ianguage       fes, Note
SOFTWARE DETAILS       language       english / german / polish         language       english / german / polish         annotation software       Yes, Note 2.0         annotations on all source       Yes, two modes         boot logo upload       Yes         boot logo upload       Yes         boot logo upload       Yes         boot logo upload       Yes         built-in response system       Yes         possibility to show send and show comments on the screen       Yes         windows software compatible with built-in annotation tool       Yes, Note         PHYSICAL SPEC       Yes, Note
languageenglish / german / polishannotation softwareYes, Note 2.0annotations on all sourcesYes, two modesboot logo uploadYesboot logo uploadYessource name changeYesbuilt-in response systemYespossibility to show send and show comments on the screenYeswindows software compatible with built-in annotation toolYes, NotePHYSICAL SPECHYSICAL SPEC
annotation softwareYes, Note 2.0annotations on all sourcesYes, two modesboot logo uploadYesSource name changeYesbuilt-in response systemYespossibility to show send and show comments on the screenYeswindows software compatible with built-in annotation toolYes, NotePHYSICAL SPECYes, Note
Annotations on all sourcesYes, two modesboot logo uploadYesSource name changeYesbuilt-in response systemYespossibility to show send and show comments on the screenYeswindows software compatible with built-in annotation toolYes, NotePHYSICAL SPECYes
boot logo uploadYessource name changeYesbuilt-in response systemYespossibility to show send and show comments on the screenYeswindows software compatible with built-in annotation toolYes, NotePHYSICAL SPECYes, Note
Source name change     Yes       built-in response system     Yes       possibility to show send and show comments on the screen     Yes       windows software compatible with built-in annotation tool     Yes, Note
built-in response system     Yes       possibility to show send and show comments on the screen     Yes       windows software compatible with built-in annotation tool     Yes, Note
possibility to show send and show comments on the screen     Yes       windows software compatible with built-in annotation tool     Yes, Note
windows software compatible with built-in annotation tool Yes, Note PHYSICAL SPEC
PHYSICAL SPEC
buttons on front 1 front button / main power switch
dimensions 1493 × 872 × 88 mm
packaging dimensions 1697 × 1039 × 220 mm
weight 44,7 kg
gross weight 59,5 kg
VESA standard 600 × 400
wall-mount included Yes
power requirements 100 - 240 V AC / 50 or 60 Hz
power consumption 0,5 W (stand-by) / 250 W (nominal power)
ENVIROMENTAL CONDITIONS
operation temperature 0°C to 40°C
operation humidity 10% to 90%
storage temperature -20°C to 60°C
storage humidity 10% to 90%
altitude max. 5000 m.a.s.l.
OTHER
diagnostic tools for quick support Yes
3 years (2 years for LCD panel) warranty Warranty may differ depending on region. Contact your local deale for more information.
Power cord (3 m), HDMI cable (3 m ), USB cable (5 m), accesories included active pen (3 pcs.), remote controller, quick guide, CD or flashdrive with drivers and software, WiFi/Bluetooth dongle



